



ProLink Specifications			
	XTV	ProLink	XXL
Height	2.95	3.95	4.95
Base Diameter	2.5	3.5	3.9
Shackle Pin Hole Diameter	.77	.92	1.05
Shear Pin Diameter - Titanium	.438	.625	.750
Internal Retaining Ring Size	.453	.625	.777
ProLink Assembly Weight	8.5 ounces	21 ounces	35 ounces
Max Cable and Synthetic Rope Diameter	1/4	3/8	1/2
Shackle Size Compatibility	1/2 or 5/8	3/4	3/4 or 7/8
ProLink Load Rating (pounds)	6000	16,000	24,000
Ultimate Failure Load (pounds)	21,000	39,000	63,000+

ProLink specifications;

Note : All ProLink models are made in the USA from billet 6000 series aluminums. All ProLink shear pins are machined from 6AL-4V grade 5 Titanium billet. All Rubber guards are made from high durometer EPDM rubber.

All dimensions in inches

<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FACTOR 55, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FACTOR 55, LLC IS PROHIBITED.</p>			<p>DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±</p>	NAME	DATE	<p>FACTOR 55</p> <p>PROLINK SPECIFICATIONS</p>
				DRAWN		
				CHECKED		
				ENG APPR.		
				MFG APPR.		
		Q.A.		COMMENTS:		
	NEXT ASSY	USED ON	FINISH			
	APPLICATION		DO NOT SCALE DRAWING			
				SIZE A	DWG. NO. 00100	REV. A
				SCALE: 1:5	WEIGHT:	SHEET 1 OF 1